

Product Specification

Product: Storage Cabinet for formalin fixed tissue specimens, extracted, 8 glazed doors

Cat.-No.: MA-0568

Filing Cabinet for formalin fixed tissue specimens, extracted, glazed doors

Type: 0568

Description

Solid cabinet corpus, self-supporting construction. Cabinet with 16 height adjustable plastic feet. Plinth panel on 3 sides with clip technology to be fastened on feet. Front plinth panel with long slots 15 x 7mm for air supply. Plinth panel height: 100mm.

Double wall construction for side walls, floor and ceiling 18mm thick. Inner and outer shelf in stainless steel 1mm, material AISI 306. Surfaces brushed (K=320) for best hygienic conditions. Inside filled with 16mm chemical stable flake board V100, cutting edges sealed with infection resistant paint. Inside filling (water resistant) glued with inner and outer panel. Floor or ceiling with extraction duct 100 x 1,5mm (70mm high). Single back wall, stainless steel 1mm, material EN / DIN AISI 306. Outer surfaces brushed / inner surfaces none-brushed.

Features

Double wall doors, 17mm thick. Inner and outer shelf 1mm, material EN / DIN AISI 306. Surface inside and outside brushed. Inside surface includes a rubber seal profile being pressed to side wall, floor and ceiling linings.

6mm security glass inserts in doors.

The doors are mounted with screw-on chromed hinges. Opening angle 165° with self-lock action.

Cabinet with 7 shelves (single wall 25mm, 1,5mm stainless steel, material EN / DIN AISI 306 perforated with 5mm holes). Distance 16 / 16mm. Upper area brushed, all sides 90° bend. Long side additionally bend to inside. Adjustable height each 50mm by means of metal pins.

Open holes are closed with plastic knobs. At hinge-areas no shelves can be mounted.



Wet specimen filing cabinet with glazed doors on both sides (room divider)

Product Specification

Below the shelves a detachable collection tray is present for safety reasons. The collection tray will hold 3 liters of liquid in case one of the container breaks or falls down. Doors with special turnrod-hinges with chromed 90°-lock-handle, The cabinet is lockable.

The cupboard may be fastened to the ceiling by pre-drilled holes.

Due to the module system each customized size can be accepted.

Technical Data

8 doors with safety-glass inserts

7 levels with adjustable shelving

1 level (lowest) as safety tank

3 walls dividing the cabinet

Air extraction value at above dimension: appr. 150m³/h

2 x air outlet (100mm AD) on top of cabinet

Dimensions: 3600(L) x 800(D) x 2600(H)mm

Weight: 750kgs

Shelving available as follows::

- flat and none-perforated
- flat and 5mm perforation
- folded back 90° and none-perforated
- folded back 90° with 5mm perforation

Country of Origin

Manufactured by MEDIS MT GmbH in Germany acc. to EN and German norms and the safety regulations of the EC and Germany!